

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
13 January 2005 (13.01.2005)

PCT

(10) International Publication Number  
**WO 2005/003647 A1**

(51) International Patent Classification<sup>7</sup>:  
2/52, 2/54

**F24J 2/36,**

(74) Agent: **GRIFFITH HACK**; GPO Box 4164, Sydney, New South Wales 2001 (AU).

(21) International Application Number:

PCT/AU2004/000884

(22) International Filing Date: 1 July 2004 (01.07.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:

2003903341

1 July 2003 (01.07.2003) AU

(71) Applicant (for all designated States except US): **SOLAR HEAT AND POWER PTY LTD** [AU/AU]; Level 25, Chifley Tower, 2 Chifley Square, Sydney, New South Wales 2000 (AU).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **LE LIEVRE, Peter** [AU/AU]; 2A Toongarah Road, North Sydney, New South Wales 2060 (AU).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

[Continued on next page]

(54) Title: CARRIER FOR A SOLAR ENERGY REFLECTOR ELEMENT



(57) Abstract: A reflector element carrier structure is disclosed for use in a solar energy reflector system. The structure comprises a reflector element (11), a corrugated platform (12) which carries the reflector element and a skeletal frame structure (13) which supports the platform. The frame structure comprises hoop-like end members (14) that are supported by rollers (18) and the rollers accommodate turning of the carrier structure about an axis of rotation that lies substantially coincident with a longitudinal axis of the reflector element (11). The combination of the corrugated platform (12), the frame structure (13) and the hoop-like end members (14) of the frame structure provide the carrier structure with a torsional stability that permits the application of turning drive from one end of the structure.

REST AVAILABLE COPY

WO 2005/003647 A1



*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**BEST AVAILABLE COPY**